

General Air & Water

EHA508
Multipurpose



Application

- For use with air or water

Markets

- Construction
- Mining
- Rental industry
- Oil and gas exploration
- In-plant air service

Construction

Tube SBR rubber

Reinforcement

High-tensile synthetic textile

Cover Abrasion, ozone, and weather resistant SBR rubber blend

Color Black (BK), Blue (BU), Gray (GY), Yellow (YW)

Operating temperature

-40°C to +100°C
(-40°F to +212°F)

Packaging

300 ft
Carton Box

Order Fulfillment

Made to Order

Number	Hose I.D.		Hose O.D.		Operating Pressure		Min. Burst Pressure		Weight		Length	
	mm	in	mm	in	bar	psi	bar	psi	kg/m	lbs/ft	mtr	ft
EHA508-04BK	6.4	0.25	13	0.52	20.0	290	60.0	870	0.13	0.09	91.4	300
EHA508-05BK	7.9	0.31	15	0.59	20.0	290	60.0	870	0.15	0.10	91.4	300
EHA508-06BK	9.7	0.38	18	0.71	20.0	290	60.0	870	0.21	0.14	91.4	300
EHA508-08BK	12.7	0.50	22	0.87	20.0	290	60.0	870	0.30	0.20	91.4	300
EHA508-10BK	15.9	0.62	25	0.98	20.0	290	60.0	870	0.35	0.24	91.4	300
EHA508-12BK	19.0	0.75	29	1.14	20.0	290	60.0	870	0.45	0.30	91.4	300
EHA508-16BK	25.4	1.00	37	1.46	20.0	290	60.0	870	0.69	0.46	91.4	300

Type of coupling

- Danfoss Quick Disconnect
- Male barbed inserts

Contact coupling manufacturer for attachment procedure and other coupling recommendations