

General Air & Water

EHA510

Multipurpose - EPDM



Application

- For use with air, oil, hot or cold water and non-aggressive chemicals
- For dust control

Markets

- Construction
- Mining
- Rental industry
- Oil and gas exploration
- In-plant air service

Construction

- Tube** EPDM rubber
- Reinforcement** High-tensile synthetic textile
- Cover** EPDM rubber
- Color** Black

Operating temperature

-40°C to +120°C
(-40°F to +248°F)

Packaging

300 ft
Carton Box

Order Fulfillment

Made to Order

Number	Hose I.D.		Hose O.D.		Operating Pressure		Min. Burst Pressure		Weight		Length	
	mm	in	mm	in	bar	psi	bar	psi	kg/m	lbs/ft	mtr	ft
EHA510-04	6.4	0.25	13	0.52	20.0	290	60	870	0.13	0.09	91.4	300
EHA510-05	7.9	0.31	15	0.59	20.0	290	60	870	0.15	0.10	91.4	300
EHA510-06	9.7	0.38	18	0.71	20.0	290	60	870	0.21	0.14	91.4	300
EHA510-08	12.7	0.50	22	0.87	20.0	290	60	870	0.30	0.20	91.4	300
EHA510-10	15.9	0.62	25	0.98	20.0	290	60	870	0.35	0.24	91.4	300
EHA510-12	19.0	0.75	29	1.14	20.0	290	60	870	0.45	0.30	91.4	300
EHA510-16	25.4	1.00	37	1.46	20.0	290	60	870	0.69	0.46	91.4	300

Type of couplings

- Hansen® Quick Connect
- Male barbed inserts

Contact coupling manufacturer for attachment procedure and other coupling recommendations

