

Concrete, Plaster & Grout

EHK005

Plaster & Grout Spraying



Application

- For high-pressure spraying plaster, grout, sand, gypsum, and ready mixed concrete

Markets

- Construction
- Cement
- Swimming pool

Construction

Tube Reinforcement Abrasion resistant SBR rubber blend

High-tensile synthetic textile and anti-static copper wire

Cover Abrasion, ozone, and weather resistant pin-pricked SBR rubber blend

Colors Black (BK), Gray (GY), Yellow (YW)

Abrasion loss value acc. DIN53516 $\leq 60\text{mm}^3$

Operating temperature

-40°C to +70°C
(-40°F to +158°F)

Packaging

100 ft
Coil on Pallet

Order Fulfillment

Made to Order

Number	Hose I.D.		Hose O.D.		Operating Pressure		Min. Burst Pressure		Minimum Bend Radius		Weight		Length	
	mm	in	mm	in	bar	psi	bar	psi	mm	in	kg/m	lbs/ft	mtr	ft
EHK005-12BK	19.0	0.75	31.0	1.22	41.0	600	123	1800	90	3.54	0.54	0.36	30.5	100
EHK005-16BK	25.4	1.00	37.0	1.46	41.0	600	123	1800	120	4.72	0.65	0.44	30.5	100
EHK005-16ABK	25.4	1.00	38.0	1.50	41.0	600	123	1800	110	4.33	0.75	0.50	30.5	100
EHK005-19BK	30.0	1.18	44.0	1.73	41.0	600	123	1800	150	10.34	0.95	0.64	30.5	100
EHK005-20BK	32.0	1.25	46.0	1.81	41.0	600	123	1800	160	6.30	1.03	0.69	30.5	100
EHK005-22BK	35.0	1.38	49.0	1.93	41.0	600	123	1800	175	6.89	1.10	0.74	30.5	100
EHK005-24BK	38.0	1.50	54.0	2.13	41.0	600	123	1800	190	7.48	1.43	0.96	30.5	100
EHK005-28BK	44.5	1.75	61.0	2.40	41.0	600	123	1800	225	8.86	1.63	1.10	30.5	100
EHK005-32BK	50.8	2.00	68.0	2.68	41.0	600	123	1800	280	11.02	1.96	1.32	30.5	100
EHK005-38BK	60.0	2.36	80.0	3.15	41.0	600	123	1800	340	13.38	2.72	1.83	30.5	100
EHK005-40BK	63.5	2.50	83.5	3.29	41.0	600	123	1800	375	14.76	2.86	1.92	30.5	100
EHK005-42BK	65.0	2.56	85.0	3.35	41.0	600	123	1800	390	15.36	2.88	1.94	30.5	100
EHK005-44BK	70.0	2.76	90.0	3.54	41.0	600	123	1800	425	16.73	2.93	1.97	30.5	100
EHK005-48BK	76.2	3.00	96.2	3.79	41.0	600	123	1800	440	17.32	3.14	2.11	30.5	100
EHK005-64BK	101.6	4.00	122.0	4.80	41.0	600	123	1800	580	22.83	4.14	2.78	30.5	100
EHK005-80BK	127.0	5.00	155.0	6.10	41.0	600	123	1800	750	29.52	6.85	4.60	30.5	100

Type of couplings

- Victaulic male NPT

Contact coupling manufacturer for attachment procedure and other coupling recommendations