

Concrete, Plaster & Grout



**EHK007**

Marauder Heavy Duty



**Application**

- For high pressure concrete pumping and placing, used in the end of concrete pump boom
- Heavy duty construction for applications needing long lasting durability

**Markets**

- Construction
- Cement placement
- Boom truck

**Construction**

**Tube** Abrasion resistant anti-static natural rubber and CBR rubber blend

**Reinforcement**

High tensile steel cords

**Cover** Abrasion, ozone and weather resistant pin-pricked special synthetic rubber

**Color** Black

**Certifications**

Meets the requirements of ASME B30.27-2014

Abrasion loss value acc. DIN53516  $\leq 60\text{mm}^3$

**Operating temperature**

-40°C to +70°C  
(-40°F to +158°F)

**Packaging**

100 ft  
Coil on Pallet

**Order Fulfillment**

Made to Stock  
Made to Order

| Number        | Hose I.D. |      | Hose O.D. |      | Operating Pressure |      | Min. Burst Pressure |      | Minimum Bend Radius |       | Weight |        | Length |     |
|---------------|-----------|------|-----------|------|--------------------|------|---------------------|------|---------------------|-------|--------|--------|--------|-----|
|               | mm        | in   | mm        | in   | bar                | psi  | bar                 | psi  | mm                  | in    | kg/m   | lbs/ft | mtr    | ft  |
| EHK007-32-100 | 50.8      | 2.00 | 70.0      | 2.76 | 86.0               | 1250 | 200                 | 2900 | 200                 | 7.87  | 3.03   | 2.04   | 30.5   | 100 |
| EHK007-40-100 | 63.5      | 2.50 | 88.0      | 3.46 | 86.0               | 1250 | 200                 | 2900 | 240                 | 9.45  | 4.48   | 3.01   | 30.5   | 100 |
| EHK007-48-100 | 76.2      | 3.00 | 102.0     | 4.02 | 86.0               | 1250 | 200                 | 2900 | 275                 | 10.83 | 5.46   | 3.67   | 30.5   | 100 |
| EHK007-64-100 | 101.6     | 4.00 | 130.0     | 5.12 | 86.0               | 1250 | 200                 | 2900 | 350                 | 13.78 | 8.46   | 5.68   | 30.5   | 100 |
| EHK007-80-100 | 127.0     | 5.00 | 155.0     | 6.10 | 86.0               | 1250 | 200                 | 2900 | 425                 | 16.73 | 9.63   | 6.47   | 30.5   | 100 |
| EHK007-96-100 | 152.4     | 6.00 | 180.0     | 7.09 | 86.0               | 1230 | 200                 | 2900 | 650                 | 25.59 | 10.99  | 7.38   | 30.5   | 100 |

**Type of couplings**

- Victaulic male NPT

Contact coupling manufacturer for attachment procedure and other coupling recommendations