

Steel Mill

EHN004

Steel Mill Heavy Duty
Cooling Water Transfer**Application**

- For discharge of cooling water
(Outside Temperature up to 600°C)

Markets

- Steel mill
- Foundries

Construction**Tube** EPDM rubber**Reinforcement**

High-tensile synthetic textile

Cover EPDM rubber and glass fiber**Colors** WhiteResistance $\leq 1 \times 10^9 \Omega/m$ **Operating temperature**

-40°C to +125°C

(-40°F to +257°F)

Packaging

100 ft

Coil on Pallet

-08, -10 Carton Box

Order Fulfillment

Made to Order

Number	Hose I.D.		Hose O.D.		Operating Pressure		Min. Burst Pressure		Weight		Length	
	mm	in	mm	in	bar	psi	bar	psi	kg/m	lbs/ft	mtr	ft
EHN004-08	12.7	0.50	22	0.87	10.0	145	30.0	435	0.34	0.23	30.5	100
EHN004-10	16.0	0.62	26	1.02	10.0	145	30.0	435	0.44	0.30	30.5	100
EHN004-12	19.0	0.75	30	1.18	10.0	145	30.0	435	0.57	0.38	30.5	100
EHN004-16	25.4	1.00	37	1.46	10.0	145	30.0	435	0.74	0.50	30.5	100
EHN004-20	32.0	1.25	45	1.77	10.0	145	30.0	435	0.99	0.67	30.5	100
EHN004-24	38.0	1.50	52	2.05	10.0	145	30.0	435	1.24	0.83	30.5	100
EHN004-28	44.5	1.75	59	2.32	10.0	145	30.0	435	1.49	1.00	30.5	100
EHN004-32	50.8	2.00	65	2.56	10.0	145	30.0	435	1.64	1.10	30.5	100
EHN004-40	63.5	2.50	79	3.11	10.0	145	30.0	435	2.15	1.45	30.5	100
EHN004-48	76.2	3.00	94	3.70	10.0	145	30.0	435	3.02	2.03	30.5	100
EHN004-64	101.6	4.00	120	4.72	10.0	145	30.0	435	3.96	2.66	30.5	100

Type of couplings

Contact coupling manufacturer for attachment procedure and other coupling recommendations