

Steam

EHS002

Textile Steam



Application

- Transfer of steam for processing products and cleaning equipment

Markets

- Refining and petrochemical
- Paper industry
- Industrial cleaning markets
- Oil and gas exploration
- Steel
- Ship building

Construction

- Tube** EPM rubber
- Reinforcement** High-tensile synthetic textile
- Cover** Pin-pricked EPDM rubber
- Color** Black

Operating temperature

-40°C to +165°C
(-40°F to +329°F)

Packaging

50 ft
Coil on Pallet

Order Fulfillment

Made to Order

Number	Hose I.D.		Hose O.D.		Operating Pressure		Min. Burst Pressure		Weight		Length	
	mm	in	mm	in	bar	psi	bar	psi	kg/m	lbs/ft	mtr	ft
EHS002-08	12.7	0.50	24.0	0.94	7.0	102	70.0	1015	0.32	0.22	15.2	50
EHS002-10	15.9	0.62	28.0	1.10	7.0	102	70.0	1015	0.46	0.31	15.2	50
EHS002-12	19.0	0.75	31.0	1.22	7.0	102	70.0	1015	0.46	0.36	15.2	50
EHS002-16	25.4	1.00	37.0	1.46	7.0	102	70.0	1015	0.61	0.41	15.2	50
EHS002-20	31.8	1.25	46.0	1.81	7.0	102	70.0	1015	0.94	0.63	15.2	50
EHS002-24	38.1	1.50	53.0	2.09	7.0	102	70.0	1015	1.17	0.79	15.2	50
EHS002-28	44.5	1.75	60.0	2.36	7.0	102	70.0	1015	1.40	0.94	15.2	50
EHS002-32	50.8	2.00	67.5	2.66	7.0	102	70.0	1015	1.75	1.18	15.2	50
EHS002-40	63.5	2.50	81.0	3.19	7.0	102	70.0	1015	2.23	1.50	15.2	50
EHS002-48	76.2	3.00	98.0	3.86	7.0	102	70.0	1015	3.31	2.23	15.2	50
EHS002-64	101.6	4.00	124.0	4.88	7.0	102	70.0	1015	4.44	2.98	15.2	50