

Beverage Discharge

EHB501

Medium Duty Beer/Wine EPDM



Application

- For discharge of beverages such as mineral water, beer, fruit juices, wine and liquor

Markets

- Food processing
- Tank truck
- Breweries
- Distilleries

Construction

Tube White non-toxic, taste and odor-free EPDM

Reinforcement

High-tensile synthetic textile

Cover EPDM rubber

Color Red (RD), Blue (BU), Black (BK)

Certifications

Regulation EC 1935/2004,
EC 2023/2006, FDA Regulation
CFR title No.21 art 177.2600

Operating temperature

-40°C to +120°C
(-40°F to +248°F)

Packaging

100 ft
Coil on Pallet

Order Fulfillment

Made to Order

Number	Hose I.D.		Hose O.D.		Operating Pressure		Min. Burst Pressure		Weight		Length	
	mm	in	mm	in	bar	psi	bar	psi	kg/m	lbs/ft	mtr	ft
EHB501-12RD	19.0	0.75	30.0	1.18	10.0	145	30.0	435	0.56	0.38	30.5	100
EHB501-16RD	25.4	1.00	37.0	1.46	10.0	145	30.0	435	0.72	0.48	30.5	100
EHB501-20RD	32.0	1.25	44.0	1.73	10.0	145	30.0	435	0.95	0.64	30.5	100
EHB501-24RD	38.0	1.50	51.0	2.01	10.0	145	30.0	435	1.19	0.80	30.5	100
EHB501-28RD	44.5	1.75	57.5	2.26	10.0	145	30.0	435	1.36	0.91	30.5	100
EHB501-32RD	50.8	2.00	65.0	2.56	10.0	145	30.0	435	1.66	1.12	30.5	100
EHB501-40RD	63.5	2.50	77.5	3.05	10.0	145	30.0	435	2.08	1.40	30.5	100
EHB501-48RD	76.2	3.00	92.0	3.62	10.0	145	30.0	435	2.68	1.80	30.5	100
EHB501-64RD	101.6	4.00	117.5	4.63	10.0	145	30.0	435	3.54	2.38	30.5	100

Type of couplings

- Cam and groove
- Combination nipple

Contact coupling manufacturer for attachment procedure and other coupling recommendations