


Suction & Discharge



H0350

Lion



Application

- For suction and discharge of non-dairy food products

Markets

- Food processing
- Tank truck
- Rail car

Construction

- Tube** Vinyl nitrile
FDA compliant
- Reinforcement** 2-ply fiber with helical wire
- Cover** Vinyl nitrile
- Color** White
- Certification** FDA compliant

Operating temperature

-40°C to +82°C
(-40°F to +180°F)

Packaging

50, 100, 150 ft

Order Fulfillment

Made to Stock

Number	Hose I.D.		Hose O.D.		Operating Pressure		Min. Burst Pressure		Minimum Bend Radius		Vacuum		Weight		Length	
	mm	in	mm	in	bar	psi	bar	psi	mm	in	kPa	in/Hg	kg/m	lbs/ft	mtr	ft
H035032-100	50.8	2.00	66.7	2.63	17.2	250	68.8	1000	127.0	5.00	94.8	28.0	2.38	1.60	30.5	100
H035048-100	76.2	3.00	92.2	3.63	17.2	250	68.8	1000	317.5	12.50	94.8	28.0	3.17	2.13	30.5	100

Type of couplings

- Cam and groove
- Combination nipple

Contact coupling manufacturer for attachment procedure and other coupling recommendations