

Sandblast

EHC500

Sandblast – 60mm³



Application

- Conveys sand or shot for cleaning purposes
- Conveys sand from sandblast equipment to clean steel or concrete before painting or sealing
- For blasting metal, stone and concrete

Markets

- Construction
- Metal working
- Ship building

Construction

Tube Static dissipating SBR rubber blend

Reinforcement

High-tensile synthetic textile with anti-static copper wire

Cover

Abrasion, ozone and weather resistant pin-pricked SBR rubber blend

Color Black

Certification

TS 5928 - EN ISO 3861

Abrasion loss value acc. DIN53516 ≤60mm³

Operating temperature

-40°C to +70°C
(-40°F to +158°F)

Packaging

100 ft
Coil on Pallet

Order Fulfillment

Made to Order

Number	Hose I.D.		Hose O.D.		Operating Pressure		Min. Burst Pressure		Minimum Bend Radius		Weight		Length	
	mm	in	mm	in	bar	psi	bar	psi	mm	in	kg/m	lbs/ft	mtr	ft
EHC500-08	12.7	0.50	25	0.98	12.1	175	36.0	522	65	2.55	0.41	0.28	30.5	100
EHC500-08A	12.7	0.50	27	1.06	12.1	175	36.0	522	60	2.36	0.50	0.33	30.5	100
EHC500-10	16.0	0.62	28	1.10	12.1	175	36.0	522	85	3.35	0.48	0.32	30.5	100
EHC500-10A	16.0	0.62	30	1.18	12.1	175	36.0	522	80	3.15	0.58	0.39	30.5	100
EHC500-12	19.0	0.75	30	1.18	12.1	175	36.0	522	100	3.94	0.49	0.33	30.5	100
EHC500-12A	19.0	0.75	31	1.22	12.1	175	36.0	522	95	3.74	0.53	0.36	30.5	100
EHC500-12B	19.0	0.75	33	1.30	12.1	175	36.0	522	90	3.54	0.65	0.44	30.5	100
EHC500-16	25.4	1.00	39	1.54	12.1	175	36.0	522	125	4.92	0.81	0.55	30.5	100
EHC500-20	32.0	1.25	48	1.89	12.1	175	36.0	522	160	6.30	1.16	0.78	30.5	100
EHC500-24	38.0	1.50	54	2.13	12.1	175	36.0	522	200	7.87	1.34	0.90	30.5	100
EHC500-24A	38.0	1.50	56	2.20	12.1	175	36.0	522	190	7.48	1.53	1.03	30.5	100
EHC500-28	44.5	1.75	60	2.36	12.1	175	36.0	522	280	11.02	1.47	0.99	30.5	100
EHC500-28A	44.5	1.75	63	2.48	12.1	175	36.0	522	270	10.60	1.82	1.22	30.5	100
EHC500-32	50.8	2.00	69	2.72	12.1	175	36.0	522	325	12.79	2.03	1.36	30.5	100
EHC500-32A	50.8	2.00	73	2.87	12.1	175	36.0	522	315	12.40	2.48	1.67	30.5	100
EHC500-40	63.5	2.50	82	3.23	12.1	175	36.0	522	400	15.70	2.63	1.77	30.5	100
EHC500-48	76.2	3.00	96	3.78	12.1	175	36.0	522	450	17.70	3.09	2.08	30.5	100
EHC500-64	101.6	4.00	122	4.80	12.1	175	36.0	522	600	23.60	4.22	2.84	30.5	100

Type of couplings

- Sandblast couplings that attach to the O.D. of hose

Contact coupling manufacturer for attachment procedure and other coupling recommendations